



# FACADE TP 52

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient  
**U<sub>cw</sub> ≥ 0.6 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing

## GLAZING

Maximum glazing: **64 mm**

Minimum glazing: **4 mm**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12152):

Water tightness (EN 12154):

Wind resistance (EN 13116):

Reference test 3.00 x 3.50 m

**Class AE**

**Class RE1350**

**PASSED** Design loading 2000 Pa-Security loading 3000 Pa

|                                  |   |
|----------------------------------|---|
| <b>PROFILE THICKNESS</b>         | Mullion 2,1 and 3 mm<br>Transom 2,1 mm  |
| <b>WINDOW MAXIMUM DIMENSIONS</b> | <p>Hidden Top Hung<br/>Width max. (L) = 2.500 mm<br/>Height max. (H) = 2.500 mm<br/>Width min. (L) = 500 mm<br/>Height min. (H) = 650 mm</p> <p>Hidden Parallel Projecting<br/>Width max. (L) = 1.500 mm<br/>Height max. (H) = 3.000 mm<br/>Width min. (L) = 450 mm<br/>Height min. (H) = 530 mm</p> <p>Hidden Side Hung or Turn&amp;Tilt<br/>Width máx. (L) = 1.400 mm<br/>Height máx. (H) = 1.900 mm<br/>Width min. (L) = 500 mm<br/>Height min. (H) = 600 mm</p> |
| <b>MAXIMUM WEIGHT</b>            | <p>200 kg Parallel projecting opening<br/>180 kg Hidden top hung opening<br/>100 Kg Tilt &amp; turn opening<br/>750 Kg Fixed glazing</p>  |

Please consult maximum dimensions according to types

|                             |   |
|-----------------------------|---|
| <b>EXTRUSION ALLOY</b>      | 6063 T-5  |
| <b>THERMAL BREAK</b>        | 6, 12 and 30 mm stackable profiles  |
| <b>GASKETS EPDM</b>         | Optionally Totally Vulcanized Corner Gasket   |
| <b>OPTIONS FOR COVERS</b>   | <p>85 mm deep elliptical cover<br/>H shape cover, 34 mm deep<br/>Rectangular cover: 14, 19, 100 &amp; 145 mm deep<br/>Flat cover<br/>Pyramid shape cover, 155 mm deep</p> |
| <b>OPENING POSIBILITIES</b> | <p>Outward: Hidden top hung<br/>Hidden parallel projecting<br/>Inward: Hidden side hung / tilt &amp; turn</p>   |

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat Standard > 60 microns

Wood effect powder coating

According to Qualideco Standard

Anodized

According to Ewwa Euras Standard

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured



Certification CWCT.  
British Standard

